

## Local extensions

- For XT 20 and EX 20 expandable versions only (1 local extension per module)
- Millenium - Millenium local link
- Doubles the hardware and software capacities
- Transparent communication between two XT 20 units
- Max. distance between two XT 20 units : 10 metres
- Cable type : screened twisted pair



### Specifications

Type	Designation	Supply	Code
XL 01	M2 - M2 local link (2 modules)	universal	88 950 200
XL 05	4 solid state outputs (8-28VDC)	universal	88 950 204
XL 06	2 relay outputs (250mA maximum)	100 → 240 V AC / 24 V AC	88 950 810

## Adjacent extensions

- For XT 20 and EX 20 expandable versions only (one adjacent extension per module)
- 6 additional inputs/outputs



### Specifications

Type	Designation	Supply	Code
XC 01	4 inputs PNP 2 relay outputs	24 V DC	88 950 210
	4 inputs 2 relay outputs	24 V AC	88 950 211
	4 inputs 2 relay outputs	100 - 240 V AC	88 950 212
	4 inputs 2 relay outputs	12 V DC	88 950 215
	4 inputs NPN 2 relay outputs	24 V DC	88 950 219

## Communication modules

- Data communication via STN or GSM modem
- Fieldbus communication using MODBUS or ASI protocol (slave module) for XT 20 and EX 20 expandable version only (one adjacent extension per module)




### Specifications

Type	Designation	Supply	Code
XC 02	AS-i communication module 24 V DC	24 V DC	88 950 213
XC 04	MODBUS communication module	24 V DC	88 950 823

### Dimensions

XC 01



XC 02 - XC 04

